

PROFESSIONAL ESD STOOL (FEET, H52-72CM)



SKU: 640354G



PROFESSIONAL ESD HIGH CHAIR - FEET

Anti-static ESD safe stool, equipped with five-spoke base, **conductive footrest and feet**.

The anatomical high backrest and seat are adjustable both in height and inclination.

Professional line chairs are characterized by **high executive quality** and multiple levels of certification.

Specifications

- Colour: **Black**
- Seat height adjustment: **52 - 72 cm**
- Backrest height adjustment (stroke 6 cm): **53 - 59 cm**
- Backrest/seat inclination adjustment: A-SYNCHRON TRI-LEVER mechanism
- **Lumbar-support seat** dimensions (WxD): 48 x 44 cm - Total depth: 47 cm
- Backrest width: 43 cm.

Technical data & compliances



Click here to read [Technical data & Compliances](#)

- **Seat:** Internal structure in multilayered beech wood, anatomically shaped, 11mm variable thickness, low formaldehyde emission according to class E1 - Outer protective shell in recyclable techno-polymer
- **Backrest:** Internal structure in recyclable techno-polymer, anatomically shaped with integrated reinforcement ribs - Outer protective shell in conductive recyclable techno-polymer
- **Padding:** Seat in PU-Flex (40mm thickness, 40g/L density) - Backrest in PU-Flex (35mm thickness, 40g/L density) - Self-extinguishing material according to UNI 9175, recyclable, without CFC/HCFC
- **ESD safe upholstery:** Composition: 99% polypropylene, 1% carbon fibre - Weight: 320 g/m² - Abrasion: UNI EN ISO 12947 (>30.000 Martindale cycles) - Flammability: IT - Class 1, EN 1021-1+2, BS 5852 Crib 5, California TB 117 - Colour: Black
- **Mechanism: AS3:** (A-SYNCHRON TRI-LEVER) - **Backrest inclination:** 12° positive, 28° negative - **Seat inclination:** 5° positive, 3° negative - Lockable in all positions - With combined activation of tilting mechanism and backrest inclination - Knob activated backrest height adjustment - According to UNI EN 1335-3
- **Lift action:** Central piston (Ø 28 mm) protected by steel tube (Ø 50 mm), chrome finish - Class 4, according to DIN 4550
- **Conductive footrest** (Ø 460 mm) - Chromed steel ring - Supports in black painted steel - Height adjustable with a knob
- **Five-spoke base** (Ø 700 mm) in die-cast aluminum with internal reinforcement ribs - Polished finish. - According to ANSI/BIFMA X5.1, BS 5459 A.5.1-A.5.5 and UNI EN 1335-3
- **Conductive feet** (H 32mm / Ø 50 mm) in black nylon
- **Manufacturer certifications:** UNI EN ISO 9001:2015 - UNI EN ISO 14001:2015 - UNI EN ISO 45001: 2018.