

## C70 SILICONE OIL (200ML)



SKU: 103149A



### C-70 SILICONE OIL

**C-70 is a medium viscosity silicone oil which penetrates and reaches the most hidden points**, spreading on the all surfaces: it effectively lubricates every part. Excellent regenerative and protective agent for natural and synthetic rubber gaskets.

C-70 is a very good solution to the friction, so it makes easier threading wires through the rubber grommets of industrial and civil electrical systems. A high protective power guarantees a longer time length to the new cables.

It's an excellent dielectric, therefore it eliminates the corona effect on the TV antenna clamps and prevents short circuits or electric leakages. High water repellent, it protects from humidity. C-70 can be also utilized as a detaching agent in the moulding of plastic. Compatible with most materials.

### Specifications

- Manufacturer: **Due-Ci Electronic**
- Packaging: **200 ml spray can**
- OZONE SAFE
- CFC AND HCFC FREE
- HIGH DIELECTRIC PROPERTIES
- SAFE FOR MOST PLASTICS
- HIGH PROTECTIVE AND LUBRICATING PROPERTIES



- REMAINS UNALTERED IN A WIDE TEMPERATURE RANGE
- HYDRO-REPELLENT AND COLOURLESS
- 100% ACTIVE PRODUCT
- FILLED WITH NON FLAMMABLE GAS
- DOUBLE-USE DISPENSER: MICROMIST + THIN CANE
- CAN BE SPRAYED UPSIDE DOWN.

**PRODUCT IDENTIFIER IN THE SAFETY DATA SHEET:**

Product name: **C-70 Silicone Oil ml.200** – Code: **C702015**

**LABEL ELEMENTS:**

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:



*Danger. Extremely flammable aerosol. Pressurised container: may burst if heated. Causes skin irritation. May cause drowsiness or dizziness. Toxic to aquatic life with long lasting effects.*

*Precautionary statements: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking - Do not spray on an open flame or other ignition source - Do not pierce or burn, even after use - Avoid release to the environment - Collect spillage - Protect from sunlight. Do not expose to temperatures exceeding 50°C.*

*Contains: Hydrocarbons C6 isoalkanes <5% n-Hexane.*

*Nominal quantity: 200ml.*

**DETAILS OF THE SUPPLIER OF THE SAFETY DATA SHEET:**

**DUE-CI ELECTRONIC Srl** – Strada del Casalino 11, 37127 – Verona (VR) - ITALY

Tel. +39 045 916251 – [www.duecielectronic.it](http://www.duecielectronic.it)