


## RTILE ESD DISSIPATIVE VYNIL FLOORING (TH.7MM)



SKU: 132119A



### R-TILE ESD SAFE FLOORING 7MM, 1MQ

**Anti-static ESD safe interlocking tiles**, thickness 7 mm.

Suitable for trolley, pallet truck and **forklift** traffic.

Selling unit: **square meter**.

#### R-Tile | ESD safe interlocking flooring

These **ESD safe interlocking floor tiles**, made up of an injection-moulded homogeneous mix of **vinyl resins and metal fibres**, are extremely easy to install and maintain. They can be laid on the existing floor: installation does not require any particular preparation of the substrate (it only needs to be smooth and clean). After installation, the floor can be walked on immediately. It's removable and it can be relocated and expanded if necessary. It is suitable also for environments with rising damp problems or characterized by the presence of machinery that cannot be moved. Like all flooring in the R-Tile line, it has excellent durability and anti-slip properties. It reduces dust, noise and fatigue and thermally insulates the floor below.

#### Specifications

- Colour: **Dark grey** (RAL 7015) - Surface: **Textured**



- Thickness: **7 mm**
- Tile useful dimensions: **500 x 500 mm**
- Tile nominal dimensions: 518 x 518 mm
- Weight: 10 kg/mq
- Electrical resistance (CEI **61340-5-1:2007**): **10<sup>5</sup> - 10<sup>7</sup> kV**
- Fire class (EN 13 501-1): Bfl-S1
- Floorscore® certified.

**ATTENTION:**

- Always purchase approximately 3% more product than the quantity needed
- **A copper grid connected with grounding points to the electrical system** must always be installed under the floor (instructions available on request).

**Accessories** (NOT included): Yellow tile with ESD symbol, Yellow access ramps (standard and angular).

**Product variations available:** Tile size 5 mm (not suitable for forklift traffic).