

DELUXE VACUUM WELDING MACHINE (600MM, 2 MODELS)



SKU: EM600DX



VACUUM SEALER WITH 600 MM SEALING BAR

Quickly creates a perfect vacuum with any type of bag

EM600DX - High-efficiency Deluxe line vacuum welding machine equipped with pneumatic nozzle and **600 mm sealing bar** (single or double).

Fully programmable, foot operated, **ESD-safe**.

It allows to carry out nitrogen cycles by adding an additional kit (NOT included).

Available models:

- **Single sealing bar** (149411S) - Suitable for ESD barrier bags with thickness **up to 90 µm**
- **Double sealing bar** (149411U) - Suitable for ESD barrier bags with thickness **up to 150 µm**.

Alternative models: With 450 mm sealing bar (single or double) - With integrated nitrogen flushing kit (450 or 600 mm sealing bar, single or double).

ATTENTION:

The machine needs external compressed air for operating, and it needs a compressor with a capacity above 250 NI/min.



The pressure of compressed air supplied to the machine should be set at 5~6.5 kgf/cm².
 If the supplied compressed air exceeds 7 kgf/cm², the machine could get damaged. In the other hand, if the compressed air is less than 4.5 kgf/cm², there can be malfunctionings.

VARIATIONS

SKU	Description	Set-up
149411S		Single sealing bar
149411U		Double sealing bar