


DELUXE VACUUM WELDING MACHINE (600MM, 2 MODELS)



SKU: EM600DX



VACUUM SEALER WITH 600 MM SEALING BAR

Quickly creates a perfect vacuum with any type of bag

EM600DX - **High-efficiency Deluxe line vacuum welding machine** equipped with pneumatic nozzle and **600 mm sealing bar** (single or double).

Fully programmable, foot operated, ESD-safe.

It allows to carry out nitrogen cycles by adding an additional kit (NOT included).

Available models:

- Single sealing bar (149411S) Suitable for ESD barrier bags with thickness up to 90 μm
- Double sealing bar (149411U) Suitable for ESD barrier bags with thickness up to 150 μm.

Alternative models: With 450 mm sealing bar (single or double) - With integrated nitrogen flushing kit (450 or 600 mm sealing bar, single or double).

ATTENTION:

The machine needs external compressed air for operating, and it needs a compressor with a capacity above 250 NI/min.



The pressure of compressed air supplied to the machine should be set at $5\sim6.5 \, \text{kgf/cm}^2$. If the supplied compressed air exceeds 7 kgf/cm², the machine could get damaged. In the other hand, if the compressed air is less than $4.5 \, \text{kgf/cm}^2$, there can be malfunctionings.

VARIATIONS

SKU	Description	Configurazione
149411S		Single sealing bar
149411U		Double sealing bar