


## ESD FLOOR WAX (5KG)



SKU: 148742A



### LIQUID STATIC DISSIPATIVE FLOOR WAX

**Anti-static ESD safe floor coating** that temporarily **gives dissipative properties to a non-antistatic floor.**

Excellent product for **maintaining conductive flooring** in operating rooms, cleanrooms and data processing centres. It may also be used for **maintaining table mats' dissipative properties.**

Rs: <  $10^{11} \Omega$ . Supplied in **5 kilos** can.

#### Method of use

- **First treatment:**  
 Thoroughly wash the floor with the stripper (El.Mi product no.: 149378A)  
 Rinse with clean water  
 When dry, apply 2 thin coats on the floor (yield: **1 lt. of product for the 2 coats on approx. 25 m<sup>2</sup>**)
- **Ordinary maintenance:**  
 Sweep the floor with a wet broom, then wash it with the detergent (El.Mi product no.: 148759A) diluted in water at 1-5% ratio.
- **Spray maintenance:**  
 Dilute the coat in water at 30% ratio, spray it on the floor and then polish with a one-brush machine provided with a suitable scotch-bride (yield: 1 lt. of product for approx. 100 m<sup>2</sup>).



*PRODUCT IDENTIFIER IN THE SAFETY DATA SHEET:*

*Product name: **Floor wax***

*LABEL ELEMENTS:*

*Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.*

*Hazard statements: (EUH210) Safety data sheet available on request.*

*DETAILS OF THE SUPPLIER OF THE SAFETY DATA SHEET:*

*Information available on the safety data sheet. Contact us to request it: Tel. +39 (0)2.269.411 – [export@elmisrl.it](mailto:export@elmisrl.it).*