


ESD FLOOR WAX (5KG)



SKU: 148742A



LIQUID STATIC DISSIPATIVE FLOOR WAX

Anti-static ESD safe floor coating that temporarily **gives dissipative properties to a non-antistatic floor.**

Excellent product for **maintaining conductive flooring** in operating rooms, cleanrooms and data processing centres. It may also be used for **maintaining table mats' dissipative properties.**

Rs: < $10^{11} \Omega$. Supplied in 5 kilos can.

Method of use

- **First treatment:**
 Thoroughly wash the floor with the stripper (El.Mi product no.: 149378A)
 Rinse with clean water
 When dry, apply 2 thin coats on the floor (yield: **1 lt. of product for the 2 coats on approx. 25 m²**)
- **Ordinary maintenance:**
 Sweep the floor with a wet broom, then wash it with the detergent (El.Mi product no.: 148759A) diluted in water at 1-5% ratio.
- **Spray maintenance:**
 Dilute the coat in water at 30% ratio, spray it on the floor and then polish with a one-brush machine provided with a suitable scotch-bride (yield: 1 lt. of product for approx. 100 m²).



PRODUCT IDENTIFIER IN THE SAFETY DATA SHEET:

*Product name: **Floor wax***

LABEL ELEMENTS:

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard statements: (EUH210) Safety data sheet available on request.

DETAILS OF THE SUPPLIER OF THE SAFETY DATA SHEET:

Information available on the safety data sheet. Contact us to request it: Tel. +39 (0)2.269.411 – export@elmisrl.it.