


## SODIUM PERSULFATE POWDER (1KG)



SKU: 101285A



### SODIUM PERSULFATE BY BUNGARD

**Sodium persulfate powder**, recommended for use in etcher tanks.

It does not crystallize and is odorless.

The copper capacity is limited to less than 30 g/l due to the long etching time.

Etching rate: approx. 1.5-7  $\mu\text{m}/\text{min}$ .

Delivery unit: **1 kg bag**.

#### Conditions of use

- Give 200-250 g of sodium persulfate to 1 litre of water
- Recommended working temperature for best results: 40-50°C.

*PRODUCT IDENTIFIER IN THE SAFETY DATA SHEET:*

Name: **Natriumpersulfat**

*LABEL ELEMENTS:*

*Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.*



Hazard pictograms:



*Danger. May intensify fire; oxidiser. Harmful if swallowed. Causes skin irritation. Causes serious eye irritation. May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction. May cause respiratory irritation.*

*Precautionary statement(s): Take any precaution to avoid mixing with combustibles. Keep away from heat/sparks/open flames/hot surfaces - No smoking - In case of inadequate ventilation wear respiratory protection - Keep/Store away from clothing/combustible materials - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing - Call a POISON CENTER or doctor/physician if you feel unwell - If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing - Store locked up.*

Nominal quantity: 1Kg.

DETAILS OF THE SUPPLIER OF THE SAFETY DATA SHEET:

**Bungard Elektronik GmbH & Co. KG** – Rilkestraße 1, D-51570 Windeck – Germany - Tel. +49 6131/19240 – [info@bungard.de](mailto:info@bungard.de).