


WX2 WELLER POWER UNIT (2-CHANNEL, 200W) | T0053420399N



SKU: T0053420399



WELLER WX CONTROL UNIT WITH 2 CHANNELS

WX 2 - Two-channel digital power unit, 200 W (255 W).

Weller product no.: **T0053420399N.**

Main features

- Robust capacitive touch screen with anti-static ESD safe glass
- Intuitive use: turn-click-wheel with enter key and finger guide
- No safety rest with Stop & Go function is needed, thanks to integrated acceleration sensor
- Visual process control via blue LED ring light
- Blue LED ring light: Light is out = Off - Light is blinking = standby or heating up - Light is on = tip ready for use
- WX soldering irons heat in ultra-quick time and can be used immediately
- Thanks to an integrated sensor, WX tools are motion activated (they consume power only when they are actually in use). Connected accessories also go into standby mode.
- Optimized precision and better stability by sensor in the soldering iron
- Specific parameterization of tool by storage medium in hand piece

- Multilingual menu navigation.

Specifications

- **Channels: 2**
- **Power: 200 W (255 W)**
- Voltage: 230 V, 50 Hz
- **Temperature range (depends on tool): 100 - 550 °C**
- Adjustable temperature range (depends on tool): 50 - 550 °C
- Temperature accuracy: ± 9 °C
- Temperature stability: ± 2 °C
- Fuse: T2A
- USB port: Yes
- Equipotential bonding: Yes
- WX compatible: Yes
- ESD-safe: Yes
- Display: 255 x 128 dots / Backlighting.